

Digital BETACAM

DIGITAL BETACAM VIDEOCASSETTE




The professional's choice for today's high-performance Digital Betacam systems

High Output and Low Error Rate for Superior Performance

To ensure high output and superior magnetic performance, D321 videocassettes feature newly developed ultra-fine, magnetic particles packed densely. The particles are approximately 20% smaller than those used in Fujifilm Betacam SP tapes, and offer+2dB higher output. New calendering technology is used to give the magnetic layer an ultrasmooth finish, thereby improving the C/N ratio and assuring a low error


rate during highdensity digital recording. In addition, a newly developed lubricant improves head contact by stabilizing tape transport over guides, rollers and head drum.

Magnetic Particles




Improved Durability & Transport Stability

To meet the demands of ENG/EFP specialists and post production professionals, Fujifilm D321 offers exceptional durability and transport stability. Durability is enhanced by a new binder that offers superior adhesion for ultrafine magnetic particles, while transport stability is boosted by a new backcoating material which keeps the friction coefficient low even during repeated passes. As a result, Fujifilm D321 easily withstands the rigorous demands of ENG/EFP field-work, and the still playback and high-speed shuttle operations of editing.







FUJIFILM D321 Digital Betacam Videocassette Technical Data

Magnetic Properties							
Coercivity (Hc)	131 kA/m						
Retentivity (Br)	270 mT						
Physical Properties							
Thickness: Magnetic Layer	3.0 μm						
: Total	14.0 μm						
Tape Width	12.65 mm						
Yield Strength	25 N						
Breaking Tensile Strength	40 N						
Performance							
Video / Audio RF Output	0 dB*						
Video / Audio C/N	0 dB*						

Sperior Storage Characteristics

To prevent oxidation during long-term storage, fujifilm D321's metal magnetic particles are covered with an ultra-thin protective layer. This ensures that the tape retains its superior magnetic characteristics during storage, while also ensuring that output remains high. In addition, exclusive Fujifilm production technology keeps tape shrinkage to an


absolute minimum, thereby eliminating tracking errors that can be caused by tape deformation.

Innovative New Hard Case Design

New hard cases feature a number of design innovations that provide added protection during outdoor use and long-term storage. These include protruding reel hub rests and raised flanges that protect videocassettes from vibration and sudden impact, and a new tongue-and-groove case seal that shuts out dust.

Color-Coded Cassettes and Cases

Exclusive color-coded cassettes and hard cases allow you to differentiate the D321 cassettes from Betacam SP, HDCAM, Betacam SX and MPEG IMX cassettes at a glance, so cassettes are M321SP(BETACAM SP) much less likely to be stored in the wrong case by mistake.





FUJIFILM D321 Digital Betacam Videocassette Line-up

perties		Casaatta	Size	Tana Langth	Recording	Dimensions		Weight	
	131 kA/m	Cassette	SIZE	Tape Length	Time	Cassette sheel	Case	(Including Case)	
	270 mT		D6	43 ⁺² ₋₀ m (141 ft.)	6 min.			250 g (0.55 lbs.)	
perties			D 12	78 ⁺² ₋₀ m (256 ft.)	12 min.			260 g (0.57 lbs.)	
gnetic Layer	3.0 μm	S	D 22	136 ⁺² ₋₀ m (446 ft.)	22 min.	156 x 96 x 25 mm		280 g (0.62 lbs.)	
al	14.0 µm		D 32	195 ⁺² ₋₀ m (640 ft.)	32 min.			290 g (0.64 lbs.)	
	12.65 mm		D 40	241 ⁺² ₋₀ m (791 ft.)	40 min.			305 g (0.67 lbs.)	
	25 N		D34L	206 ⁺² ₋₀ m (676 ft.)	34 min.	254 x 145 x 25 mm	271 x 162 x 33 mm	640 g (1.41 lbs.)	
le Strength	40 N		D64L	382 ⁺² ₋₀ m (1,253 ft.)	64 min.			690 g (1.52 lbs.)	
		L		557 ⁺² ₋₀ m (1,827 ft.)			271 X 102 X 33 11111	740 g (1.63 lbs.)	
RF Output	0 dB*		D124L	732 ⁺² ₋₀ m (2,402 ft.)	124 min.			790 g (1.74 lbs.)	
	0 4P*	Note: Figures are typical values based on ELLIEU M's standard management presedures							

Note: Figures are typical values based on FUJIFILM's standard measurement procedures. The figures marked with * are comparisons with the FUJIFILM Digital Betacam reference tape Specifications are subject to change without notice

🖭 FUJIFILM

FUJI PHOTO FILM CO., LTD.

26-30, NISHIAZABU 2-CHOME, MINATO-KU, TOKYO 106-8620, JAPAN

Fuji Photo Film U.S.A., Inc.

Magnetic Markets Division 200 Summit Lake Drive, 2nd Floor Valhalla, New York 10595, U.S.A.

Fuji Photo Film Canada Inc. 600 Suffolk Court Mississauga, O Fuji Photo Film do Brasil Ltda.

Ontario, L5R 4G4, Canada

da Vereador Jose Diniz 3400, Campo Belo, Sao Paulo, CEP 04604-901, SP, Brasil

Fuji Magnetics G.m.b.H.

leve. Germanv

Fujistrasse 1, D-47533 Kleve, Germany Fuji Photo Film (UK) Ltd. Fuji Film House, 125 Finchley Road, Swiss Cottage, London NW3 6HY, U.K. FUJIFILM Regional Services (Singapore) Pte Ltd. 10 New Industrial Road Singapore 536201