

Universal 5-year vinyl for flat and slightly curved indoor and outdoor surfaces



Self-Adhesive outdoor

euromedia 2D Vinyl P-WB

The versatility of euromedia 2D Vinyl P-WB is impressive. The self-adhesive, calendared 5-year polymeric film can be used for a large number of high quality solvent, latex and UV printing applications and is particularly suitable for applying to flat and slightly curved surfaces. Excellent lie-flat properties allow problem-free printing and finishing. The particularly white, glossy surface guarantees reproduction of bright colours and excellent contrast.

euromedia 2D Vinyl P-WB is very dimensionally stable, even over long periods of time and under adverse conditions. If you prefer a material that is particularly easy to apply and reliably obliterates even high contrast surfaces, we recommend euromedia 2D SmartApply. For short-term applications we advise you to use monomeric euromedia vinyls.

Watch our video about the 2D Vinyl P-WB [here](#)

Dimensions

75mic - 1067mm(42') - 45,7m
 75mic - 1370mm(54') - 45,7m
 75mic - 1520mm(60') - 45,7m

Product Code

70100105152
 70100104961
 70100112187



Hints & Tips

Even if the surface appears dry and you can handle the finished graphics without a problem, we recommend that you wait 24 hours before processing so that the solvents can evaporate completely out of the material. If you would like to finish 2D Vinyl P-WB with a laminate, euromedia 2D Laminate is perfect for the job.

euromedia 2D Vinyl P-WB

Product Properties

Applications

- indoor
- outdoor
- 2D wraps
- trade fairs
- 3-5 years durability

Properties

- permanent adhesive
- polymeric vinyl

Processing Tips

We basically recommend that the print is left to dry out for 24 hours before finishing.

Storage

The product should be stored in its original packaging at a room temperature of 15°C - 25°C and 40 - 60% relative humidity.



Specifications

Material	Polymeric, calendered PVC
Ink	Solvent, Latex, UV
Surface	White
Gloss Level	Glossy
Thickness	75 mic
Tensile strength	>2,3 kg/cm
Adhesive type	Solventbased (transparent)
Adhesive strength	2.5 lbs/in; 0.45 kg/cm
Release value	39 g/cm (90°, 760 cm/min)
Temperature resistency	-29°C to 65°C
Application temperature	16°C to 32°C
Others	Dimensional stability: 0.64 mm
Shelf life	1 year

Note

This information relates to the current state of our knowledge and is given without obligation to provide you with information about our products and their applications. The information we give does not absolve you from carrying out your own trials and tests of the suitability of our products for your intended application. We reserve the right to carry out modifications, which will result in an improvement to the product.

euromedia

FUJIFILM Deutschland

Niederlassung der FUJIFILM Europe GmbH
 Heesenstraße 31 40549 Düsseldorf DE
 Tel: +49 211-5089-326
 Fax: +49 211-5089-287
 grafische_systeme@fujifilm.de