

PVC-coated banner material,  
B1/M1 for indoor rollups and  
displays



Indoor Banner

## euromedia Display Banner FR

Unique display substrate for producing solvent-printed rollups etc. Totally unmatched in terms of dense blacks, saturated colours, photo-realistic image reproduction. The very fine, elegant honeycomb structure plus a non-reflective PVC finish deliver optimum print results of presentation quality.

Ditto for perfectionists: euromedia Display Banner FR lies flat. Even under adverse conditions. Thanks to a patented manufacturing process. In addition: Easy to transport and space-saving in weight and volume. Top product solution! For extremely price sensitive RollUp jobs, we recommend euromedia Solvent PP Banner.

### Dimensions

270g - 0900mm(35') - 25m  
270g - 1100mm(44') - 25m  
330g - 1350mm(53') - 25m  
330g - 1600mm(63') - 25m  
330g - 2500mm(98') - 50m

### Product Code

70100098262  
70100098958  
70100098286  
70100098229  
70100098241



### Hints & Tips

You can really get the best `icing-on-the-cake performance` out of euromedia Display Banner, if you print with profiling. Euromedia profiles are available to download online

## euromedia Display Banner FR

### Product Properties

#### Applications

- indoor
- displays
- trade fairs

#### Properties

- fire classification B1
- fire classification M1
- cold cutting
- can be eyelet
- can be stitched
- can be welded

#### Processing Tips

We basically recommend that the print is left to dry out for 24 hours before finishing.

#### Storage

The product should be stored in its original packaging at a room temperature of 15°C - 25°C and 40 - 60% relative humidity.



#### Specifications

Material	Polyester/ PVC coated
Ink	Solvent, Latex, UV
Flame retardancy	M1, B1
Gloss Level	Satin matt
Total thickness	~ 0,3 mm
Weight	330 g/m <sup>2</sup>
Yarn	1100x1100 dtex
Tensile strength	140/150 daN/5 cm
Tearing Strength	> 150 N Kette > 180 N Schuss
Temperature resistency	-20°C to +70°C

#### Note

This information relates to the current state of our knowledge and is given without obligation to provide you with information about our products and their applications. The information we give does not absolve you from carrying out your own trials and tests of the suitability of our products for your intended application. We reserve the right to carry out modifications, which will result in an improvement to the product.

**euromedia**

#### FUJIFILM Deutschland

Niederlassung der FUJIFILM Europe GmbH  
 Heesenstraße 31 40549 Düsseldorf DE  
 Tel: +49 211-5089-326  
 Fax: +49 211-5089-287  
 grafische\_systeme@fujifilm.de